



IW MODEL	H MM
12	950
15	1150
18	1350
24	950
30	1150
36	1350
48	950
60	1150
72	1350
90-936	1350

IW MODEL	DIMENSIONS MM			D BSP	E BSP	F BSP	G MM
	A	B	C				
12-18	1585	430	515	0.75	0.75	1.5	850
24-72	1590	610	685	0.75	0.75	2	1150
90-108	1590	695	885	0.75	0.75	2	1500
126-216	1695	810	930	0.75	1.5		80 1650
234-324	1695	960	1060	0.75	1.5		100 1450
360-504	1695	1095	1300	0.75	2		100 1750
576-720	1710	1195	1600	1	2		125 1850
792-936	1920	1380	1700	1	3		150 1950

CONNECTIONS ARE BSP FEMALE TAPER OR FLANGED BS4504 PN16

NOTE (IW48 TO IW936) - FLOW TEMPERATURE DETECTOR (NOT SHOWN) SUPPLIED WITH 1.5 METRE FLEXIBLE CONDUIT AND 1/2" BSP POCKET FOR INSERTION IN FLOW PIPEWORK BETWEEN BOILER AND ANY VALVES

IN THE INTEREST OF CONTINUOUS DEVELOPMENT COLLINS WALKER LTD RESERVE THE RIGHT TO CHANGE THE SPECIFICATION WITHOUT NOTICE

COLLINS WALKER Ltd

THIS DRAWING IS THE PROPERTY OF COLLINS WALKER LTD IN WHOM THE COPYRIGHT SUBSISTS

TITLE GENERAL ARRANGEMENT
IW IMMERSION ELEMENT
WATER BOILERS

SCALE INTS
DRAWN M J DODD
CHK'D T AKHTAR
APP'D C GODDARD
DATE 23.08.2006

JOB NO. CLIENT.
SUPERSEDES DWG 11100-2

NO SHTS 1

DWG NO A165
SHT 1

ALL DIMENSIONS IN MM ORIGINAL DWG SIZE A3 DO NOT SCALE DWG

REV'N	B	GENERAL REV.	REV'N	REV'N	REV'N	REV'N	REV'N	REV'N
DRAWN	MJD		DRAWN		DRAWN		DRAWN	
CHK'D	TA		CHK'D		CHK'D		CHK'D	
APP'D	CG		APP'D		APP'D		APP'D	
DATE	20.10.96		DATE		DATE		DATE	